



EN 14785
BlmSchV Stufe 2
Regensburger BStV / Aachener BStV / Munchener BStV
ART.15a B-VG / Klimafonds / LRV
4 stelle DM.186 / Conto Termico 2.0



get

(Max) nominal heat output	8 kW
Minimum heat output	2.5 kW
Efficiency at Max	90.4 %
Efficiency at Min	92 %
Energy Efficiency Class (A++ / G scale)	A+
Energy Efficiency Index (EEI)	120 %
Seasonal space heating energy efficiency (η_s)	80 %
Temperature of exhaust smoke at Max	196 °C
Temperature of exhaust smoke at Min	103 °C
Particulate/OGC / Nox (nominal at 13%O₂)	16 - 1 - 137 mg/Nm³
CO at 13% O₂ at Min and at Max	0.055 - 0.003 %
CO₂ at Min and at Max	7.4 - 14.1 %
Recommended draught at Max power	10 Pa
Minimum draught allowed for minimum power	5 Pa
Mass of smoke at Min and at Max	2.5 - 4.3 g/sec
Hopper capacity	32 l
Fuel dimensions	Ø 6mm L 3 ÷ 40mm
Hourly consumption at Min and at Max	0.6 - 1.8 kg/h *
Autonomy at Min and at Max	35 - 12 h *
Heatable volume m³	145 - 229 - 400 **
Combustion air inlet	Ø 50 mm
Air inlet	80 cm²
Smoke outlet	Ø 80 mm
Nominal electrical power (EN 60335-1).	70 W (max 350 W)
Supply voltage and frequency	230 Volt / 50 Hz
Net weight	130 kg
Distance from combustible material (back/side/under)	50 mm / 100 mm / 0 mm
Distance from combustible material (front/ceiling)	800 mm / 1000 mm

* Data that may vary depending on the type of pellets used.

**Heatable volume based on the requested power per m³ (respectively 55-35-20 W/m³)